Shenzhen DXM Technology Co., Ltd

PTC thermistor

PTC Thermistor for degaussing loop of colour TV chromoscope-MZ71 series

Specification&Part no.

Item	Part No.	Rated Zero Power Resistance R(N)(Ω)	Curie temperature T c (℃)	Max Operating Voltage Vmax (V)	Current Attenuation Characteristics			Condition		Dimension （mm）			
					Initial Current (Ap-p)	After 3 Sec. (mAp-p)	After 60 Sec. (mArms)	Rated Vol. VN(V)	Load Resistance RL(Ω)	D±10	T		
1	MZ71-3ROX140		40:60	140	≥26	≤300	≤15	100,120	3	12	6.0	0.6	7.5
2	MZ71-5RON140	5±30%	40:60	140	≥35	≤300	≤15	100,120	3	13	6.0	0.6	7.5,10
3	MZ71-7ROM140	7±20%	40:60	140	≥25	≤300	≤15	100,120	10	14	6.0	0.6	7.5,10
4	MZ71-9ROM270	9±20%	40:60	270	≥25	≤300	≤12	220	10	14	6.0	0.6	7.5,10
5	MZ71-12RM270	12±20%	40:60	270	≥20	≤240	≤12	220	10	14	6.0	0.6	7.5,10
6	MZ71-14RM270	14±20%	40:60	270	≥20	≤200	≤12	220	10	14	6.0	0.6	7.5,10
7	MZ71-18RM270	18±20%	40:60	270	≥20	≤250	≤12	220	10	14	6.0	0.6	7.5,10
8	MZ71-22RM270	22±20%	40:60	270	≥20	≤150	≤12	220	10	14	6.0	0.6	7.5,10

Note： 1. R 25 resistance tolerance can be selected per customer’s requirement.

2. Encapsulation mode can be made per customer’s requirement.

3. Wire shape kinked form can be selected.

QQ:1794139339
Skype:dxm_sales

Shenzhen DXM Technology Co., Ltd.
Website: http://www.dxmht.com

Mobile: 86-13823707943
Email: info@dxmht.com